




LEGEND
 ARMSTRONG CEILING
 BCLA 236 CFL WEB2

Recess mounting, indirect lighting, CFL decorative luminaire with perforated concave louver



NOMINAL DIMENSIONS IN mm Tolerance +/-5

Application

- Commercial complexes,
- Showrooms and Airport lounges,
- Computer centers,
- Banks and hospitals,
- Conference halls,
- Design offices,
- Control rooms and laboratories, etc.

Specification

- Epoxy broken white powder coated CRCA sheet steel housing.
- Detachable CRCA concave shaped perforated (Honey Comb) diffuser.
- Accessories for 2 x CFL 36W prewired upto terminal block.
- Wired with HF electronic ballast.
- Also available with 40W/55W CFL-4P Lamp.

Electrical Data

Cat. Ref.	Lamp Type & Wattage (W)	Nominal Voltage (V)	Mains Current in Amps. at 240 V	Power Factor
BCLA 236 CFL WEB2	2 x CFL 'L' 36/4P	240	0.311	≥ 0.95

Data subject to variation due to change/improvement in the design, materials and processes.

<p>BAJAJ LUMINAIRES Making the difference</p>	DRAWN	VDS	16-10-2007	FOR - STD.
	CHECKED	DVRS		REV - 1 DATE-24-01-2008
	APPROVED	CRR		DRG.No
	DATA SHEET RELEASED ON DT-			BCLA 236 CFL WEB2- 001