




INDUSTRIAL LIGHTING  
PLASMA  
BPRF 02 236 F LHD

Recess mounting FRONT OPENING clean room luminaire suitable for twin FTL



Dimensions in mm Tolerance +/-5mm

### Applications

- Interior illumination in Pharmaceuticals, Food & Beverage industries, Electronic component manufacturing areas, laboratories, etc.

### Specification

- Epoxy white powder coated CRCA sheet steel housing
- High quality pre-anodised aluminium reflector
- Control gear and new generation accessories with < 10 % THD electronic ballast mounted on removable gear tray and pre-wired upto terminal block
- PMMA acrylic cover is sealed with bottom frame & specially developed non-hygroscopic gasket to ensure foolproof dust/ particle protection
- Maintenance from front side
- Re-lamping through hingeable front cover fixed to the housing with loss proof SS screws.
- Hardware S.S
- Environment protection:- IP65

### Electrical Data

Product Code	Cat. Ref.	Lamp Type & Wattage (W)	Nominal Voltage (V)	Mains Current in Amps. at 240 V	Power Factor
530859	BPRF 02 236 F LHD	2 x FTL 36	240	0.303	≥ 0.99

Data subject to variation due to change/improvement in the design, materials and processes.

<p><b>BAJAJ LUMINAIRES</b> Making the difference</p>	DRAWN	VDS	05-07-2007	FOR – STD.
	CHECKED	DVRS		REV - 1 DATE-02-05-2009
	APPROVED	CRR		DRG. No
	DATA SHEET RELEASED ON DT-			BPRF 02 236 F LHD-001
BAJAJ ELECTRICALS LIMITED 15/17, SANT SAVTA MARG, REAY ROAD, MUMBAI-400 010.				* E-mail : <a href="mailto:luminaires@bajajelectricals.com">luminaires@bajajelectricals.com</a>