



LEGEND

BTSMU 236 MSS

Surface/ Pendant mounted 2X36 W mirror optic FTL luminaire



NOMINAL DIMENSIONS IN mm Tolerance +/-5 mm

Specifications:

- Main luminaire body is extruded aluminium white powder coated finish.
- Specially designed PVC end caps.
- High quality pre-anodised aluminium mirror reflector.
- Serrated matt anodised aluminium transverse fins.
- Reflector assembly is held to body with push fit arrangements.
- Wired with high frequency HF ballast.
- MSS (Millennium Suspension System)-Adjustable stainless steel rope assembly.

Benefits:

- Well balanced light distribution
- Slick & elegant in shape
- Luminaire body is corrosion resistant & durable
- High light output with low brightness
- Suitable for Uplighting , by pendent lighting
- Ultra thin body height occupies less space
- Easy to install and maintain

Electrical Data

Product Code	Cat. Ref.	Lamp Type & Wattage (W)	Nominal Voltage (V)	Mains Current In Amps. At 240 V	Capacitor Mfd.	Power Factor
160736	BTSMU 236 MSS	FTL 2x36	240	0.43	8.00	≥ 0.90

Data subject to variation due to change/improvement in the design, materials and processes.

	DRAWN	VDS	21-01-2003	FOR – STD.
	CHECKED	DVRS	21-01-2003	REV - 1 DATE-24-01-2008
	APPROVED	CRR	21-01-2003	DRG.No
	DATA SHEET RELEASED ON DT-			BTSMU 236 - 001